


Part Number	Trade Size	O.D.	I.D.
V06AEA1	1/2"	0.820" Min 0.840" Max	0.622" Min 0.642" Max
V06AGA1	3/4"	1.030" Min 1.050" Max	0.820" Min 0.840" Max
V06BAA1	1"	1.290" Min 1.315" Max	1.041" Min 1.066" Max
V06BCN1	1 1/4"	1.630" Min 1.660" Max	1.380" Min 1.410" Max
V06BEN1	1 1/2"	1.865" Min 1.900" Max	1.575" Min 1.600" Max
V06CAN1	2"	2.340" Min 2.375" Max	2.020" Min 2.045" Max

UL Listed (UL1660)
 UL Category Code DX0Q
 CSA Certified
 For Use See NEC Article 356
 Do not use PVC Cement with this product
 Use only approved liquidtight fittings
 May be used outdoors exposed to sunlight
 May be direct buried
 600 volt maximum
 Minimu installation temperature 0.4°F (-18°C)
 Maximum ambient temperature 167°F (75°C)
 UL Rated: 80°C dry, 60°C wet, 70°C oil resistant
 Product is TYPE B LFNC
 Not plenum rated

 CANTEX INC. Fort Worth, TEXAS		
ENVIROFLEX Type LFNC-B Liquidtight Flexible Nonmetallic Conduit		