

CANTEX PVC cements and primers are for use on rigid PVC Electrical conduit and fittings. We recommend the use of CANTEX PVC cements and primers with CANTEX PVC products since they are especially formulated for use with our products.

DO NOT USE FOR WATER, SEWER OR DWV INSTALLATIONS.

Low Voc Conduit Cement No. 99



| Part Number | Size | Carton Qty. |
|-------------|----------|-------------|
| 7210601 | 1/2 Pint | 24 |
| 7210602 | Pint | 12 |
| 7210603 | Quart | 12 |

Low Voc Conduit Cement No. 99 - Gray



| Part Number | Size | Carton Qty. |
|-------------|----------|-------------|
| 7210501 | 1/2 Pint | 24 |
| 7210502 | Pint | 12 |
| 7210503 | Quart | 12 |

Low Voc Conduit All Weather Cement



| Part Number | Size | Carton Qty. |
|-------------|----------|-------------|
| 7210411 | 1/2 Pint | 24 |
| 7210412 | Pint | 12 |
| 7210413 | Quart | 12 |

Operating temperature range is -15°F to 110°F.

Conduit Primer No. 10



| Part Number | Size | Carton Qty. |
|-------------|-------|-------------|
| 7211303 | Quart | 12 |

Operating temperature range is 50°F to 100°F.

ESTIMATED SOLVENT REQUIREMENT PER 1,000 FEET IN QUARTS One weld per 20 feet

| Pipe Size | 1/2" | 3/4" | 1" | 1-1/4" | 1-1/2" | 2" | 2-1/2" | 3" | 4" | 5" | 6" |
|-----------|------|------|-----|--------|--------|----|--------|-------|----|-------|----|
| Cement | 1/2 | 1/2 | 1/2 | 1 | 1 | 1 | 1-1/2 | 1-1/2 | 2 | 2-1/2 | 4 |
| Primer | 1/2 | 1/2 | 1/2 | 1 | 1 | 1 | 1-1/2 | 1-1/2 | 2 | 2-1/2 | 4 |

ENT NO. 50 Low Voc Cement Solvent Cement for EZ-FLEX ENT



| Part Number | Size | Carton Qty. |
|-------------|-------|-------------|
| 7210402 | Pint | 12 |
| 7210403 | Quart | 12 |